

ważny od 12.05.2016

Numer zamówieniowy - stary format	Numer zamówieniowy	W magazynie	Make to order (MTO)	Czas realizacji MTO w tygodniach	Kategoria	Opis/Parametry techniczne	EAN	Sugerowana cena sprzedaży netto PLN	Sugerowana cena sprzedaży brutto PLN	Grupa rabatowa	Data aktualizacji	Uwagi
0607160501	0.607.160.501	x			drill	T-grip drill, 320W - 0.43 hp, 2800 rpm, keyed 3/8" chuck, R only, 0.68 kg.	3165140111133	929	1 142		12.05.2016	
0607160502	0.607.160.502	x			drill	T-grip drill, 320W - 0.43 hp, 2800 rpm, keyless 3/8" chuck, R only, 0.68 kg.	3165140111140	1 002	1 232		12.05.2016	
0607160504	0.607.160.504	x			drill	T-grip drill, 320W - 0.43 hp, 850 rpm, keyed 3/8" chuck, R only, 0.59 kg.	3165140111154	1 178	1 449		12.05.2016	
0607160505	0.607.160.505		x	4	drill	T-grip drill, 320W - 0.43 hp, 850 rpm, keyless 3/8" chuck, R only, 0.82 kg.	3165140111171	1 329	1 634		12.05.2016	
0607160509	0.607.160.509		x	4	drill	T-rip drill, 320W - 0.43 hp, 750 rpm, Keyed 3/8" chuck, R/L, 0.82 kg.	3165140111188	1 312	1 613		12.05.2016	
0607160511	0.607.160.511	x			drill	T-rip drill, 320W - 0.43 hp, 2200 rpm, keyed 3/8" chuck, R/L, 0.68 kg.	3165140111157	1 002	1 232		12.05.2016	
0607557501	0.607.557.501	x			rotary hammer	Rotary Hammer, 740W - 1.0 hp, 850 rpm, 3/4" capacity in concrete, impact rate: 3900 rpm, SDS-plus chuck, 3 kg	3165140111195	5 096	6 267		12.05.2016	
0607252103	0.607.252.103	x			grinder	Straight grinder, 550W - 0.74 hp, 21,000 rpm, 6 mm collet, 1.1 kg., locking switch, max. stone diameter 1.6"	3165140111225	1 664	2 047		12.05.2016	
0607260100	0.607.260.100	x			grinder	Straight grinder, 320W - 0.43 hp, 21,000 rpm, 6 mm collet, 0.59 kg., sliding switch, max. stone diameter 1.6"	3165140111201	929	1 142		12.05.2016	
0607260101	0.607.260.101		x	4	grinder	Straight grinder, 320W - 0.43 hp, 21,000 rpm, 1/4" collet, 0.59 kg., sliding switch, max. stone diameter 1.6"	3165140111218	929	1 142		12.05.2016	
0607260110	0.607.260.110		x	4	grinder	Straight grinder SET, 320W - 0.43 hp, 21,000 rpm, 6 mm collet, 0.59 kg., sliding switch, max. stone diameter 1.6"	3165140252416	1 045	1 285		12.05.2016	
0607350198	0.607.350.198	x			palm sander	Random orbit palm sander, 12000 rpm, velcro pad 15-hole, 5/16"-24 spindle, 0.61 kg., max. disc diameter: 3 in.	3165140621342	1 002	1 232		12.05.2016	
0607350199	0.607.350.199	x			palm sander	Random orbit palm sander, 12000 rpm, velcro pad 15-hole, 5/16"-24 spindle, 0.71 kg., max. disc diameter: 6 in.	3165140621359	1 002	1 232		12.05.2016	
0607350200	0.607.350.200	x			palm sander	Random orbit palm sander, 12000 rpm, velcro pad 15-hole, 5/16"-24 spindle, 0.71 kg., max. disc diameter: 6 in.	3165140624657	1 002	1 232		12.05.2016	
0607352113	0.607.352.113		x	4	grinder	Angle grinder, 550W - 0.74 hp, 12,000 rpm, M14 spindle, deadman switch, 1.32 kg., max. wheel diameter: 5"	3165140111256	1 711	2 105		12.05.2016	
0607352114	0.607.352.114		x	4	grinder	Angle grinder, 550W - 0.74 hp, 7000 rpm, M14 spindle, deadman switch, 1.32 kg., max. wheel diameter: 5"	3165140111270	1 402	1 724		12.05.2016	
0607450593	0.607.450.593	x			impact wrench	Standard Impact Wrench, range: 1300 Nm/960 ft-lbs., 3100 rpm, 1" square drive, R/L, 9.57 kg. For M33 screws.	3165140111362	5 895	7 251		12.05.2016	
0607450622	0.607.450.622	x			impact wrench	Standard Impact wrench, range: 900 Nm/664 ft-lbs., 4,500 rpm, 3/4" square drive, 4.99 kg.	3165140346160	2 086	2 565		12.05.2016	
0607450626	0.607.450.626	x			impact wrench	Standard compact impact wrench, range: 120 Nm/89 ft-lbs., 10,000 rpm, 3/8" square drive, R/L, 1.5 kg. For M14 screws.	3165140448680	529	651		12.05.2016	
0607450627	0.607.450.627	x			impact wrench	Standard compact impact wrench, range: 120 Nm/89 ft-lbs., 10,000 rpm, 1/2" square drive, R/L, 1.5 kg. For M14 screws.	3165140448697	602	740		12.05.2016	
0607450628	0.607.450.628	x			impact wrench	Standard impact wrench, range: 310 Nm/229 ft-lbs., 7,000 rpm, 1/2" square drive, R/L, 2.31 kg. For M18 screws.	3165140448703	645	793		12.05.2016	
0607450629	0.607.450.629	x			impact wrench	Impact wrench set, includes: 0 607 450 627 std, 1/2" square drive wrench, case, extension, 5 sockets.	3165140453028	778	957		12.05.2016	
0607450794	0.607.450.794	x			ratchet wrench	Standard ratchet wrench, range: 70 Nm/52 ft-lbs., 160 rpm, 3/8" square drive, R/L, 1.32kg. For M10 screws.	3165140364614	912	1 121		12.05.2016	
0607450795	0.607.450.795	x			ratchet wrench	Standard ratchet wrench, range: 70 Nm/52 ft-lbs., 160 rpm, 1/2" square drive, R/L, 1.32 kg. For M10 screws.	3165140364621	912	1 121		12.05.2016	
0607460001	0.607.460.001		x	4	screwdriver	Depth-sensitive pistol-grip screwdriver, max 8 Nm/71 in-lbs, 320W - 0.4hp, 750 rpm, 1/4" female hex drive, R/L, 0.82 kg.	3165140111324	2 533	3 115		12.05.2016	
0607460400	0.607.460.400		x	4	screwdriver	Pistol-rip screwdriver, range: 1.5-10 Nm/13-89 in-lbs, 320W - 0.4 hp, 750rpm, ratcheting cushion clutch, 1/4" female hex drive, R/L, 0.91 kg. For M6 screws.	3165140111300	1 625	1 999		12.05.2016	
0607460401	0.607.460.401	x			screwdriver	Straight screwdriver, range: 1.5-10 Nm/13-89 in-lbs, 380W - 0.5hp, 900 rpm, ratcheting cushion clutch, 1/4" female hex drive, R/L, 1 kg. For M6 screws.	3165140111317	1 776	2 184		12.05.2016	
0607450614	0.607.450.614	x			impact wrench	Magnesium Pistol Impact wrench, max 150 Nm, 10,000 rpm, 3/8" square drive, R/L, 1.32 kg. For M14 screws.	3165140346108	1 243	1 529		12.05.2016	
0607450615	0.607.450.615	x			impact wrench	Magnesium Pistol Impact wrench, max 350 Nm, 7000 rpm, 1/2" square drive, R/L, 2.31 kg. For M18 screws.	3165140346115	1 668	2 052		12.05.2016	
0607450618	0.607.450.618	x			impact wrench	Magnesium Pistol Impact wrench, max 300 Nm, 7000 rpm, 1/2" square drive, extended anvil, R/L, 2.6 kg. For M18 screws.	3165140346139	1 952	2 401		12.05.2016	
0607450616	0.607.450.616	x			impact wrench	Magnesium Pistol Impact wrench, max 900 Nm, 4500 rpm, 3/4" square drive, R/L, 4.99 kg. For M27 screws.	3165140346122	2 739	3 369		12.05.2016	
0607450619	0.607.450.619	x			impact wrench	Magnesium Pistol Impact wrench, max 850 Nm, 4500 rpm, 3/4" square drive, extended anvil, R/L, 5.89 kg. For M27 screws.	3165140346146	3 023	3 718		12.05.2016	
0607561116	0.607.561.116	x			jigsaw	Jigsaw, 400W - 0.54 hp, 2200 strin PL 2012 mit "AFO" markiertes/min. deadman switch, 1.81 kg.	3165140111423	2 043	2 512		12.05.2016	
0607561118	0.607.561.118	x			jigsaw	Jigsaw, 400W - 0.54 hp, 2200 strin PL 2012 mit "AFO" markiertes/min. lever switch, 1.81 kg.	3165140111430	2 043	2 512		12.05.2016	
0607595100	0.607.595.100	x			rubber cutter	Foam Rubber Cutter, 120W - 0.16 hp, 3800 strin PL 2012 mit "AFO" markiertes/min, max. blade length of 12", 1.18 kg. Blades & guide not included; see accessory pages for details.	3165140111515	4 115	5 062		12.05.2016	
0607560500	0.607.560.500	x			chisel hammer	Chisel Hammer, 3600 impacts/min, accepts hex and round shafts, 1 kg.	3165140111386	602	740		12.05.2016	
0607560501	0.607.560.501	x			chisel hammer	Chisel Hammer set, includes: 0 607 560 500 hammer, case, 3 chisels.	3165140111379	778	957		12.05.2016	
0607560502	0.607.560.502	x			descaler	Needle Descaler, 3900 impacts/min, 1.91 kg.	3165140111393	1 045	1 285		12.05.2016	
0607950938	0.607.950.938				balancer	Balancer, capacity: 0.9-1.18 kg, 31 in. drop, 1.18 kg., hose pulley	3165140123051	886	1 090		12.05.2016	
0607950939	0.607.950.939	x			balancer	Balancer, capacity: 1.18-2.18 lbs, 31 in. drop, 1.18 kg., hose pulley	3165140123068	886	1 090		12.05.2016	
0607950950	0.607.950.950	x			balancer	Balancer, capacity: 0.5kg min, 1.2kg max, 2000 mm 0.6kg (Replacement for 0.607.950.920)	3165140624305	288	354		12.05.2016	
0607950951	0.607.950.951	x			balancer	Balancer, capacity: 1.0kg min, 2.0kg max, 2000 mm 0.6kg	3165140624725	288	354		12.05.2016	
0607950952	0.607.950.952	x			balancer	Balancer, capacity: 0.3kg min, 1.5kg max, 1600 mm 0.5kg (Replacement for 0.607.950.921)	3165140624732	335	413		12.05.2016	
0607950953	0.607.950.953	x			balancer	Balancer, capacity: 1.2kg min, 2.5kg max, 1600 mm 0.5kg (Replacement for 0.607.950.922)	3165140624749	335	413		12.05.2016	
0607950954	0.607.950.954	x			balancer	Balancer, capacity: 2.0kg min, 5.0kg max, 3000 mm 3.3kg (Replacement for 0.607.950.924)	3165140629546	912	1 121		12.05.2016	
0607950955	0.607.950.955	x			balancer	Balancer, capacity: 4.0kg min, 8.0kg max, 3000 mm 3.7kg (Replacement for 0.607.950.925)	3165140629553	1 002	1 232		12.05.2016	
0607950956	0.607.950.956	x			balancer	Balancer, capacity: 7.0kg min, 10.0kg max, 3000 mm 3.7kg (Replacement for 0.607.950.926)	3165140629560	1 019	1 253		12.05.2016	
0607950958	0.607.950.958	x			balancer	Balancer, capacity: 1.2kg min, 2.8kg max, 1600 mm 1.4kg	3165140629584	619	762		12.05.2016	

hex = Internal hex output drive  
sq = Square output drive  
\*\* = 0.9 seconds trigger repeat protection  
\*\* = with sheet metal, construction and woodscrews  
CwK = Keyed Chuck  
KC = Keyless Chuck  
P+LS. = Push and Leverstart combined  
P = Push Start  
QCC = Quick Change Chuck  
hex = Internal hex output drive  
sq = Square output drive  
\*\* = 0.9 seconds trigger repeat protection  
\*\* = with sheet metal, construction and woodscrews  
CwK = Keyed Chuck  
KC = Keyless Chuck  
P+LS. = Push and Leverstart combined  
P = Push Start  
QCC = Quick Change Chuck  
hex = Internal hex output drive  
sq = Square output drive  
\*\* = 0.9 seconds trigger repeat protection  
\*\* = with sheet metal, construction and woodscrews  
CwK = Keyed Chuck  
KC = Keyless Chuck  
P+LS. = Push and Leverstart combined  
P = Push Start  
QCC = Quick Change Chuck  
hex = Internal hex output drive  
sq = Square output drive  
\*\* = 0.9 seconds trigger repeat protection  
\*\* = with sheet metal, construction and woodscrews